

# EVOLUTE CLEANTECH SOLUTIONS PVT.LTD



## MATERIAL SAFETY DATA SHEET

Revision Date: 08/02/2023

### MSDS

Print Date: 08/02/2023 Version: 1.0

#### Section 1 - Identification of the Substance/Preparation and of the Company/Undertaking

Product Name: **Li-Ion Battery Pack  
3.62V, 4800 mAh with PCM**

Model No: **LLI-CC24800-1S1P**

Chemical Family: **N/A**

Trade Name: **Evolute Cleantech Solutions Pvt.Ltd  
125, Madhuram Industrial Estate,  
Sativali Road, Vasai (E) – 401 208.**

Phone Number: **+91-250-6633500 / 9819704020**

Email: **info@evolute.in**

#### Section 2 - Hazards Identification

Preparation hazards and classification	Not dangerous with normal use. Do not dismantle, open or shred the Cylindrical Lithium Ion Rechargeable Cell ingredients contained within or their ingredients products could be harmful.
Appearance, Color, and Odor	Solid object with no odor, no color.
Primary Route(s) of Exposure	These chemicals are contained in a sealed enclosure. Risk of exposure occurs only if the cell is mechanically, thermally or electrically abused to the point of compromising the enclosure. If this occurs, exposure to the electrolyte solution contained within can occur by Inhalation, Ingestion, Eye contact and Skin contact
Potential Health Effects:	<b>ACUTE (short term):</b> see Section 8 for exposure controls In the event that this battery has been ruptured, the electrolyte solution contained within the battery would be corrosive and can cause burns. <b>Inhalation:</b> Inhalation of materials from a sealed battery is not an expected route of exposure. Vapors or mists from a ruptured battery may cause respiratory irritation. <b>Ingestion:</b> Swallowing of materials from a sealed battery is not an expected route of exposure. Swallowing the contents of an open battery can cause serious chemical burns of mouth, esophagus, and gastrointestinal tract. <b>Skin:</b> Contact between the battery and skin will not cause any harm. Skin contact with contents of an open battery can cause severe irritation or burns to the skin. <b>Eye:</b> Contact between the battery and the eye will not cause any harm. Eye contact with contents of an open battery can cause severe irritation or burns to the eye. <b>CHRONIC (long term):</b> see Section 11 for additional toxicological data

# EVOLUTE CLEANTECH SOLUTIONS PVT.LTD



## MATERIAL SAFETY DATA SHEET

Revision Date: 08/02/2023

### MSDS

Print Date: 08/02/2023 Version: 1.0

Medical Conditions Aggravated by Exposure	Not applicable
Reported as carcinogen	Not applicable

### Section 3 – Composition/Information on Ingredients

#### Li-ion Battery Pack

LLI-CC24800-1S1P: 3.62V 4800mAh with PCM

#### Technical Parameters of Li-Ion Pack:

Nominal Voltage	(Battery Pack)	3.62V	
Nominal Capacity	(Battery Pack)	4800mAh	Typical
No of Cell		1Cells	L-21700 type
Individual Cell Capacity		3.6V 4800mAh	L-21700 type
Discharge End Voltage		2.5V	2.5V Per Cell
Charge Upper Limit Volt		4.2V	
Charge Current	Standard Charge Current	2500mA	
Discharge Current	Standard Discharge Current	1000mA	
	Max Current (Peak)	5000mA	
Operation Temperature	Charge	0 ~ 55 C	
	Discharge	- 20 ~ 50 Deg. C	
Storage Temperature	in one month	- 20 ~ 50 Deg. C	
	in three month	- 20 ~ 45 Deg. C	

#### PCM Features:

SI No	Contents		Criteria
1	Voltage	Battery voltage	3.62V (1 series cells)
2	Over Charge Protections	Over Voltage Protection	4.2V(x number of series cells)
3	Over Discharge Protections	Under Voltage Protection	2.5V(x number of series cells)
4	Protections	Other Protections	Over charge and discharge and short circuit

# EVOLUTE CLEANTECH SOLUTIONS PVT.LTD



## MATERIAL SAFETY DATA SHEET

Revision Date: 08/02/2023

### MSDS

Print Date: 08/02/2023 Version: 1.0

### Testing Condition:

Maximum Charge	Constant current and constant voltage (CC/ CV) Constant Current:1000mA Upper limit Voltage: 4.2V
Maximum Discharge	Constant current discharge(CC) Constant current: 2500mA End voltage: 2.5V

### Mechanical Specification:

Dimension	76mm x 25mmΦ $\pm$ 1mm
Weight	75gm
Casing	Soft Pack with wire length of 50mm and Molex 3 pin connector with NTC.

### Section 4 – First Aid Measures

<b>Inhalation</b>	If contents of an opened battery are inhaled, remove source of contamination or move victim to fresh air. Obtain medical advice.
<b>Skin contact</b>	If skin contact with contents of an open battery occurs, as quickly as possible remove contaminated clothing, shoes and leather goods. Immediately flush with lukewarm, gently flowing water for at least 30 minutes. If irritation or pain persists, seek medical attention. Completely decontaminate clothing, shoes and leather goods before reuse or discard.
<b>Eye contact</b>	If eye contact with contents of an open battery occurs, immediately flush the contaminated eye(s) with lukewarm, gently flowing water for at least 30 minutes while holding the eyelids open. Neutral saline solution may be used as soon as it is available. If necessary, continue flushing during transport to emergency care facility. Take care not to rinse contaminated water into the unaffected eye or onto face. Quickly transport victim to an emergency care facility.
<b>Ingestion</b>	If ingestion of contents of an open battery occurs, never give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Have victim rinse mouth thoroughly with water. DO NOT INDUCE VOMITING. Have victim drink 60 to 240 mL (2-8oz.) of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Have victim rinse mouth with water again. Quickly transport victim to an emergency care facility.

### Section 5 – Fire-fighting Measures

Flammable Properties	In the event that this battery has been ruptured, the electrolyte solution contained within the battery would be flammable. Like any sealed container, battery cells may rupture when exposed to excessive heat; this could result in the release of flammable or corrosive materials.
----------------------	--

# EVOLUTE CLEANTECH SOLUTIONS PVT.LTD



## MATERIAL SAFETY DATA SHEET

Revision Date: 08/02/2023

### MSDS

Print Date: 08/02/2023 Version: 1.0

Suitable extinguishing Media	Use extinguishing media suitable for the materials that are burning.
Unsuitable extinguishing Media	Not available.
Explosion Data	<b>Sensitivity to Mechanical Impact:</b> This may result in rupture in extreme cases <b>Sensitivity to Static Discharge:</b> Not Applicable
Specific Hazards arising from the chemical	Fires involving Cylindrical Lithium Ion Rechargeable Cell are controlled with water. When water is used, however, hydrogen gas may evolve. In a confined space, hydrogen gas can form an explosive mixture. In this situation, smothering agents are recommended to extinguish the fire
Protective Equipment and precautions for firefighters	As for any fire, evacuate the area and fight the fire from a safe distance. Wear a pressure-demand, self-contained breathing apparatus and full protective gear. Fight fire from a protected location or a safe distance. Use NIOSH/MSHA approved full-face Self-contained breathing apparatus (SCBA) with full protective gear.
NFPA	Health: 0 Flammability: 0 Instability: 0

## Section 6 – Accidental Release Measures

Personal Precautions, protective equipment, and emergency procedures	Restrict access to area until completion of clean-up. Do not touch the spilled material. Wear adequate personal protective equipment as indicated in Section 8.
Environmental Precautions	Prevent material from contaminating soil and from entering sewers or waterways.
Methods and materials for Containment	Stop the leak if safe to do so. Contain the spilled liquid with dry sand or earth. Clean up spills immediately.
Methods and materials for cleaning up	Absorb spilled material with an inert absorbent (dry sand or earth). Scoop contaminated absorbent into an acceptable waste container. Collect all contaminated absorbent and dispose of according to directions in Section 13. Scrub the area with detergent and water; collect all contaminated wash water for proper disposal.

# EVOLUTE CLEANTECH SOLUTIONS PVT.LTD



## MATERIAL SAFETY DATA SHEET

Revision Date: 08/02/2023

### MSDS

Print Date: 08/02/2023 Version: 1.0

## Section 7 – Handling and Storage

Handling	<p>Don't handle Cylindrical Lithium Ion Rechargeable Cell with metalwork. Do not open, disassemble, crush or burn battery. Ensure good ventilation/ exhaustion at the workplace.</p> <p>The battery pack is not charged above the maximum charging rating under any circumstances.</p> <p>Prevent formation of dust.</p> <p>Information about protection against explosions and fires: Keep ignition sources away- Do not smoke.</p>
Storage	<p>If the Cylindrical Lithium Ion Rechargeable Cell is subject to storage for such a long term as more than 3 months, it is recommended to recharge the Cylindrical Lithium Ion Rechargeable Cell periodically.</p> <p>3 months: -10°C~+40°C, 45 to 85%RH</p> <p>And recommended at 0°C~+35°C for long period storage.</p> <p>The capacity recovery rate in the delivery state (50% capacity of fully charged) after storage is assumed to be 80% or more.</p> <p>Do not store Cylindrical Lithium Ion Rechargeable Cell haphazardly in a box or drawer where they may Short-circuit each other or be short-circuited by other metal objects.</p> <p>Keep out of reach of children.</p> <p>Do not expose Cylindrical Lithium Ion Rechargeable Cell to heat or fire. Avoid storage in direct sunlight.</p> <p>Do not store together with oxidizing and acidic materials.</p>

## Section 8 – Exposure Controls and Personal Protection

Engineering Controls	<p>Use local exhaust ventilation or other engineering controls to control sources of dust, mist, fumes and vapor.</p> <p>Keep away from heat and open flame. Store in a cool, dry place.</p>
Personal Protective Equipment	<p><b>Respiratory Protection:</b> Not necessary under normal</p>

# EVOLUTE CLEANTECH SOLUTIONS PVT.LTD



## MATERIAL SAFETY DATA SHEET

Revision Date: 08/02/2023

### MSDS

Print Date: 08/02/2023 Version: 1.0

	<p>conditions.</p> <p><b>Skin and body Protection:</b> Not necessary under normal conditions, Wear neoprene or nitrile rubbergloves if handling an open or leaking battery.</p> <p><b>Hand protection:</b> Wear neoprene or natural rubber material gloves if handling an open or leaking battery. <b>Eye Protection:</b> Not necessary under normal conditions, Wear safety glasses if handling an open or leaking battery.</p>
Other Protective Equipment	Have a safety shower and eye wash fountain readily available in the immediate work area.
Hygiene Measures	Do not eat, drink, or smoke in work area. Maintain good housekeeping.

## Section 9 - Physical and Chemical Properties

Physical State	Form: Solid
	Color: Blue
	Odor: Odorless
Change in condition:	
pH, with indication of the concentration	Not applicable
Melting point/freezing point	Not available.
Boiling Point, initial boiling point and Boiling range:	Not available.
Flash Point	Not available.
Upper/lower flammability or explosive limits	Not available.
Vapor Pressure:	Not applicable
Vapor Density: (Air = 1)	Not applicable
Density/relative density	Not available.

# EVOLUTE CLEANTECH SOLUTIONS PVT.LTD



## MATERIAL SAFETY DATA SHEET

Revision Date: 08/02/2023

### MSDS

Print Date: 08/02/2023 Version: 1.0

Solubility in Water:	Insoluble
n-octanol/water partition coefficient	Not available.
Auto-ignition temperature	130°C
Decomposition temperature	Not available.
Odour threshold	Not available.
Evaporation rate	Not available.
Flammability (soil, gas)	Not available.
Viscosity	Not applicable

## Section 10 - Stability and Reactivity

Stability	The product is stable under normal conditions.
Conditions to Avoid (e.g. static discharge, shock or vibration)	Do not subject Cylindrical Lithium Ion Rechargeable Cell to mechanical shock. Vibration encountered during transportation does not cause leakage, fire or explosion. Do not disassemble, crush, short or install with incorrect polarity. Avoid mechanical or electrical abuse.
Incompatible Materials	Not Available
Hazardous Decomposition Products	This material may release toxic fumes if burned or exposed to fire
Possibility of Hazardous Reaction	Not Available

## Section 11 - Toxicological Information

# EVOLUTE CLEANTECH SOLUTIONS PVT.LTD



## MATERIAL SAFETY DATA SHEET

Revision Date: 08/02/2023

### MSDS

Print Date: 08/02/2023 Version: 1.0


Irritation	Risk of irritation occurs only if the cell is mechanically, thermally or electrically abused to the point of compromising the enclosure. If this occurs, irritation to the skin, eyes and respiratory tract may occur.
Sensitization	Not Available
Neurological Effects	Not Available
Teratogenicity	Not Available
Reproductive Toxicity	Not Available
Mutagenicity (Genetic Effects)	Not Available
Toxicologically Synergistic Materials	Not Available

## Section 12 - Ecological Information

General note:	Water hazard class 1(Self-assessment): slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Anticipated behavior of a chemical product in environment/possible environmental impact/ecotoxicity	Not Available
Mobility in soil	Not Available

Persistence and Degradability	Not Available
Bioaccumulation potential	Not Available
Other Adverse Effects	Not Available



<p style="text-align: center;"><b>EVOLUTE CLEANTECH SOLUTIONS PVT.LTD</b></p>	
<p style="text-align: center;"><b>MATERIAL SAFETY DATA SHEET</b></p>	<p>Revision Date: 08/02/2023</p>
<p style="text-align: center;"><b>MSDS</b></p>	<p>Print Date: 08/02/2023 Version: 1.0</p>

## Section 13 – Disposal Considerations

Product disposal recommendation: Observe local, state and federal laws and regulations.

Packaging disposal recommendation: Be aware discarded batteries may cause fire, tape the battery terminals to insulate them. Don't disassembly the battery. Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local, state and federal laws and regulations.

## Section 14 – Transport Information

The Cylindrical Lithium Ion Rechargeable Cell (CMINR21700F2) had passed the UN 38.3 test and is classified as non-dangerous goods and also complies with the UN Recommendations on the Transport of Dangerous Goods; IATA Dangerous Goods regulations, and applicable U.S. DOT regulations for the safe transport of Cylindrical Lithium Ion Rechargeable Cell.

The Cylindrical Lithium Ion Rechargeable Cell is transported according to the PACKING INSTRUCTION 965 Section I B of IATA DGR 63rd edition (Proper shipping name and UN ID number: LITHIUM ION BATTERIES, UN No.: UN3480). However, the Cylindrical Lithium Ion Rechargeable Cell may also be transported according to the PACKING INSTRUCTION 966 Section II of IATA DGR 63rd edition (Proper shipping name and UN ID number: LITHIUM ION BATTERIES PACKED WITH EQUIPMENT, UN No.: UN3481) or PACKING INSTRUCTION 967 Section II of IATA DGR 63rd edition (Proper shipping name and UN ID number: LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT, UN No.: UN3481).

More information concerning shipping, testing, marking and packaging can be obtained from label master at <http://www.labelmaster.com/>.

Each package must be labeled with a Lithium Battery handling label.

Li-ion batteries treated as "Non-regulated goods" under the United Nations Recommendations on the Transport of Dangerous Goods, Special Provision 188, provided that packaging is strong and prevent the products from short-circuit.


With regard to transport, the following regulations are cited and considered:

The International Civil Aviation Organization (ICAO) Technical Instructions (2021-2022 edition).

The International Air transport Association (IATA) Dangerous Goods Regulations (63rd edition).

The International Maritime Dangerous Goods (IMDG) Code (Amdt. 40-20).

The US Hazardous Materials Regulation (HMR) pursuant to a final rule issued by RSPA

<p style="text-align: center;"><b>EVOLUTE CLEANTECH SOLUTIONS PVT.LTD</b></p>	
<p style="text-align: center;"><b>MATERIAL SAFETY DATA SHEET</b></p>	<p>Revision Date: 08/02/2023</p>
<p style="text-align: center;"><b>MSDS</b></p>	<p>Print Date: 08/02/2023 Version: 1.0</p>

The Office of Hazardous Materials Safety within the US Department of Transportations' (DOT) Research and Special Programs Administration (RSPA)

## Section 15 - Regulatory Information

OSHA hazard communication standard (29 CFR 1910.1200)

Hazardous                      V                      Non-hazardous


## Section 16 - Other Information

The information above is believed to be accurate and represents the best information currently available to us. However, Raion makes no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. Although reasonable precautions have been taken in the preparation of the data contained herein, it is offered solely for your information, consideration and investigation. This material safety data sheet provides guidelines for the safe handling and use of this product; it does not and cannot advise on all possible situations, therefore, your specific use of this product should be evaluated to determine if additional precautions are required.

The data/information contained herein has been reviewed and approved for general release on the basis that this document contains no export controlled information.

Prepared By: Quality Engineer

Approved By: Quality Manager

<p><b>EVOLUTE CLEANTECH SOLUTIONS PVT.LTD</b></p>	
<p><b>MATERIAL SAFETY DATA SHEET</b></p>	<p>Revision Date: 08/02/2023</p>
<p><b>MSDS</b></p>	<p>Print Date: 08/02/2023 Version: 1.0</p>

**Disclaimer:**

No warranty, expressed or implied, or merchantability, fitness for a particular purpose or otherwise is made, except that the products herein discussed comply with the chemical description on the labels. Buyer assumes risks of the use, storage and handling. Evolute Cleantech Solutions Pvt. Ltd shall not be liable for any incidental or consequential damages arising directly or indirectly in connection with the purchase, use, storage or handling of this product. The information contained herein is, to the best of our knowledge, true and accurate. However, all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. We disclaim any liability incurred in connection with the use of these data or suggestions. This information is not to be taken as a license to operate under, or a recommendation to infringe any patent(s). The observance of all regulations and patents is the responsibility of the user. No agent, representative or employee of this company is authorized to vary any terms of this notice.